


GPIB to USB interface.

Specification of NI GPIB-USB-HS

Performance		
GPIB	3-wire	up to 1830 kbytes/ s
	HS488	up to 7230 kbytes/ s
Power Requirements		
USB bus-powered device	+5 V (VBUS)	140 mA, Typical; 500 mA, Maximum
Physical Characteristics		
Dimensions		10.7 cm × 6.6 cm × 2.6 cm (4.2 in × 2.6 in. × 1.0 in.)
Weight		180 g (6.3 oz), includes USB cable weight
Connector	GPIB	IEEE 488 24-pin connector
	USB	USB standard Type A plug
Jackscrew	Thread	M3.5 × 0.6
	Torque	0.56 N. m (5.0 lb .in), maximum
Environment		
Operating ambient temperature		0 °C to 55 °C (Tested in accordance with IEC 60068-2-1 and IEC 60068-2-2.)
Operating relative humidity		10% to 90%, noncondensing (Tested in accordance with IEC 60068-2-56.)
Storage ambient temperature		-20 °C to 70 °C (Tested in accordance with IEC 60068-2-1 and IEC 60068-2-2.)
Storage relative humidity		5% to 95%, noncondensing (Tested in accordance with IEC 60068-2-56.)


(Dr. D. P. Singh)

Specification of NI-488.2 Software

Compatible OS	Windows, macOS, and Linux
Requirement	Functionalization of GPIB-USB-HS hardware using NI-488.2 software


(Dr D. P. Singh)